



Hustler Z4 48/54/60

Features and Benefits

- Kawasaki Commercial V-twin engines
- Welded steel decks. NOT STAMPED!
- Commercial hydrostatic transmissions for true zero turning radius maneuverability
- Commercial duty, serviceable deck spindles
- Heavy-duty, remote air cleaner for increased engine protection.
- Heavy-duty, 11-gauge, full-height rear bumper provides protection for the engine and exhaust, retains the ease of maintenance.
- Toughest frame, front forks, and deck in the industry
- Wide stance, low center of gravity for unmatched stability on slopes
- Simplest maintenance in the industry
- 10-gallon fuel capacity with built-in sight line
- Silky-smooth SmoothTrak™ steering with patented automatic park brake system
- Foldable certified ROPS and seat belt.
- 48", 54" or 60" side-discharge/mulching decks
- "Drive-straight" adjustment.
- Standard hour meter.

Best warranty in the business

- Limited Lifetime warranty on the leading edge of the deck
 - Limited Lifetime warranty on tractor frame
 - A limited 2-year commercial warranty – parts and labor*
- *See your local Hustler dealer for complete warranty details*





Z4™ 48/54/60 Specifications

Engine

Model	23/48	25/54	27/60
Make	Kawasaki	Kawasaki	Kawasaki
Horsepower	23	25	27
No. of Cylinders	2	2	2
Max. Torque	39.8 ft lbs @ 2400 rpm	41 ft lbs @ 2400 rpm	52.9 ft lbs @ 2000 rpm

Z4™ Seating Options

Engine	23	25	27
Z4 Standard Seat	•	•	•
Z4 Suspension Seat	•	•	•

Starter 12-volt (.8 kw) (see engine manufacturer specs)

Ignition Electronic

Charging System 12-volt, 15-amp (see engine manufacturer specs)

Fuel Unleaded gasoline (see engine manufacturer specs)

Fuel Filter Replaceable, automotive-type

Air Cleaner Heavy-duty, remote mounted

Cooling Air cooled. Fly-wheel fan

Governor Mechanical

Traction Drive System

Type Dual hydrostatic. Individual pumps power two direct-drive wheel motors. Hydrostatic system operates on 20W50 motor oil.

Pumps Two variable displacement, axial-piston type. Each pump powers one drive-wheel motor. Hydro-Gear PJ 12cc Pump

Pump Drive V-belt drive from engine crankshaft

Hydraulic Lines Stainless-steel, high-pressure lines with Parker Seal-Lok™ O-Ring Face-Seal fittings. Hydraulic lines and fittings guaranteed to never leak!

Final Drive Direct-drive high-torque wheel motors. One for each drive wheel. Hydro-Gear HGM 15 E

Filter Spin-on type; 40 micron

Ground Speed Infinitely variable: 0-10 mph (0-12.9 kph) forward, 0-5 mph (0-8 kph) reverse

Steering Twin-lever SmoothTrak™ steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

Turning Radius True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

Brakes

Service: Hydrostatic dynamic braking

Parking: Automotive-style drum brakes. When steering levers are placed in park position, integral park brakes are automatically engaged.

Mower Drive Single V-belt drive from engine with electric clutch. Spring tension idler for extended belt life

Tires

Front: 13 x 5 – 6, rib tread

Drive: 48 & 54: 23 x 9.5 x 12, 60: 24 x 12.0 x 12

Capacities Fuel System: 10 US gal (37.85 l)

Dimensions

Height: 52.5 in (133.35 cm) With ROPS down
67.9 in (172.47 cm) With ROPS up

W/48 in Deck

Length: 74.88 in (189.02 cm)

Overall width: 53.7 in (136.4 cm) w/discharge chute up

Tire-to-tire width: 47 in (119.38 cm)

Weight: 995 lbs (378 kg)

W/54 in Deck

Length: 74.88 in (189.02 cm)

Overall width: 60.0 in (152.4 cm) w/discharge chute up

Tire-to-tire width: 47 in (129.54 cm)

Weight: 1015 lbs (390 kg)

W/60 in Deck

Length: 76.75 in (193 cm)

Overall width: 66 in (168 cm) w/discharge chute up

Tire-to-tire width: 51 in (129.54 cm)

Weight: 1040 lbs (401 kg)

Safety Features Operator presence system connected to deck and drive clutches. Stabilizer rollers at rear of tractor

Seat Molded, cool-grey vinyl seat with adjustable armrests. Fore and aft sliding adjustment.

Construction Mainframe is 1.5 in x 1.5 in x .188 in (3.8 cm x 3.8 cm x .48 cm) square steel tubing. Front caster wheels mounted with roller bearings on each wheel. Front caster forks are .375 in (.95 cm) steel

Deck Lift Foot-operated deck height adjustment. Pin for setting height, detent for transport position

Controls Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes

Indicators Engine warning light (low oil pressure)

Cup Holder Two cup holders molded into the left side fuel tank. Accommodates nearly any cup size.

ROPS Certified, 2-post, foldable ROPS

Decks 48", 54" or 60" Side-Discharge Decks

Type Free-floating mower using three blades with center blade to the front. Mower is suspended at the corners. Includes 4 deck-mounted rollers to improve flotation in rolling and uneven terrain

Deck Lift Raise and lower deck from driver's seat with simple foot-operated deck height adjustment. Pin for setting height, transport position. Change cutting heights, climbing curbs and trailer more easily

Construction. .125 in (.317 cm) welded steel. Solid 1 in x .375 (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. Commercial-style

box-section reinforced front edge. Reinforcements welded onto spindle mount areas. Molded rubber discharge chute.

Cutting Heights Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (3.81 cm to 11.43 cm)

Mowing Blades Heavy-duty, heat-treated, high-lift Fusion™ blades

48 in: 16.5 in x 2.5 in x .20 in

54 in: 18.5 in x 2.5 in x .20 in

60 in: 20.5 in x 2.5 in x .20 in

Blade Tip Speed

48 in: 18,306 fpm (at 3500 RPM engine speed)

54 in: 18,464 fpm

60 in: 18,331 fpm

Blade Drive V-belt drive to all three spindles. Spring tension idler pulleys
Spindles Aluminum casting with steel shafts and sealed ball bearings

Flotation Suspended mower floats on four spring-assisted chains. 4 anti-scalp wheels are standard

Width of Cut

48 in: 47.1 in (120 cm)

54 in: 53.1 in (135 cm)

60 in: 59.1 in (150 cm)

Trim Capacity (left side)

48 in: 0.5 in (1.25 cm) w/9.5 in tire = 0.75 in (1.90 cm)

54 in: 2.5 in (6.5 cm) w/9.5 in tire = 4.75 in (12.06 cm)

60 in: 5.9 in (15 cm) w/12 in tire = 5.75 in (14.60 cm)

Accessories

Flex Forks™ Shock-absorbing front caster forks for a smooth ride and smoother cut

Mulch Kit Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

Catcher Commercial-duty, 6.5 bushel, rear-mounted, two-bag catcher

No-Flat Caster Tires (Semi Pneumatic)

Gator™ Blades Patented mulching blade design

Wavy Blades Improved performance for mulching

Other Accessories Light Kit, Steering Lever Extension Kit

Personalized Bumper Have your name laser-cut into the rear bumper of your mower. Ask your dealer for details.

Specifications subject to change without notice.