

P231

With Shindaiwa's Low Emissions P231 Pole Pruner, No Pruning Project is Out Of Reach.

*Meets the new, more
demanding emission standards*

Designed to improve any landscaper's versatility, Shindaiwa's new P231 pole pruner makes short work out of tall branches. This new addition to the Shindaiwa professional line delivers the performance, reliability and convenience needed to prune tree limbs and brush in those hard-to-reach places. Shindaiwa engines have evolved to meet environmental standards by fine-tuning and by using a two-stage catalyst in the muffler that cleans and reduces exhaust emissions. The result: a machine that delivers all the power Shindaiwa is famous for but is also cleaner and more efficient.

Features and Benefits

- **EPA Phase 1 and CARB. Tier II certified.**
- **The proven 231 series 2-cycle engine** develops 1.1 horsepower for maximum performance and long life in commercial applications.
- **Rotary-valve Walbro carburetor** provides easy starts in the toughest conditions
- **An efficient chain saw assembly** makes short work of the toughest projects.

- **The positive lock split-boom feature of the powerhead** allows the operator to quickly and easily disassemble the unit for easy transport and storage.
- **One-piece transistor-controlled ignition system** provides years of trouble-free operation time.
- **Automatic adjustable oiler.**
- **Chain tensioning** can be accomplished easily in the field.
- **Convenient controls** make operation a snap!
- **7-day money back guarantee!**

Specifications

| | |
|-------------------------------|--|
| Displacement | 1.4 cu in./22.5 cc |
| Bore and Stroke | 1.3 in. x 1.1 in. 32 mm x 28 mm |
| Output @7500 RPM | 1.1 hp/0.8 kw |
| Dry Weight w/o Bar & Chain | 13.4 lbs./6.1 kg |
| Overall Length w/10" Bar Assy | 110.4 in./2804 mm |
| 10" Standard Bar Length | 10 in./255 mm |
| Drive Links | 39 |

| | |
|-------------------------|---|
| 8" Optional Bar Length | 7.8 in./199 mm |
| Drive Links | 33 |
| 12" Optional Bar Length | 11.8 in./300mm |
| Drive Links | 44 |
| Carburetor | Walbro WYL-122 with primer |
| Fuel Tank Capacity | 22.7 oz./670 ml |
| Oil requirements | .. Oil must meet or exceed ISO-L-EGD and or JASO FL performance requirements. |

Standard Equipment

- 10-inch narrow kerf bar and chain
- 3.8-inch rim sprocket
- Scabbard
- Maintenance tool kit

Specifications subject to change without notice.

shindaiwa
ONE

Shindaiwa ONE oil exceeds ISO requirements. Shindaiwa strongly recommends the use of Shindaiwa ONE in all low emission engines.

shindaiwa

Shindaiwa Inc.
P.O. Box 2810
Tualatin, Oregon 97062
phone 503 692-3070
fax 503 692-6696
www.shindaiwa.com

First to Start. Last to Quit.

